

PX3 - 401

Lubricants are our specialty. PX3 lubrication" has more than 10 years experience of manufacturing and supplying lubricants in Iran.

PX3 lubrication" is one of the most trusted brands in Iran along with world's latest technology has steady efforts in progressing and innovation.

Anti-seize paste for tool joints

Advantages and benefits:

CERAMIC ANTI-SEIZE COMPOUND is a non-metallic anti-seize compound and assembly paste. Containing micro ceramic particles in a phyllosilicate vehicle compounded in a synthetic base fluid with a non-melt thickener. The compound fills surface irregularities and prevents both leaks and the intrusion of contaminants. The major advantage of this ceramic compound is that galvanic corrosion is prevented when dissimilar metals are joined. Use on brake assemblies, all studs, nuts, bolts and other threaded connections, including exhaust systems. Assembly is made easier and threaded couplings can be secured uniformly with optimum torque. After long periods of service in quite arduous conditions of heat, pressure and vibration, components can be readily broken out without damage or distortion.

Applications:

Use on brake assemblies, all studs, nuts, bolts and other threaded connections, including exhaust systems. Assembly is made easier and threaded couplings can be secured uniformly with optimum torque. After long periods of service in quite arduous conditions of heat, pressure and vibration, components can be readily broken out without damage or distortion.

Technical data:

SPECIFICATION	Methods	Conditions	Unit	Value
Base oil Viscosity	din 51 562-1	40 °C	cst	180
Base oil Type				Mineral oil
Pour point	DIN ISO 3016	3°C step	°C	-45
Thickener Type				inorganic
Consistency	DIN 51 818	DIN ISO 2137	NLGI- class	1-2-3
Worked penetration	DIN ISO 2137	60 Dh	0,1 mm	310 – 340 NLGI 1 265 – 295 NLGI 2 220 – 250 NLGI 3
Drop point	DIN ISO 2176		°C	185 NLGI 1 190 NLGI 2 190 NLGI 3
Additives				Ceramic, ...
Minimum service temperature				-30 °C
Maximum service temperature				300 °C
Color				Red pink

PX3 LUBRICATION - IRAN

Phone: (+98) 8645283020
Phone: (+98) 9194365681
Phone: (+98) 9125343599

Fax: (+98) 8645283020

Email: petrolubs@gmail.com

PX3 LUBRICATION - EU

Phone: (+36) 30 7935015

Email: info@px3lube.com

